

TV / audio amplifier “Sonumaxx 2.4“ A-4108-0**Technical specifications and features:**

- Size of transmitter (Height x Width x Depth): 128 mm x 128 mm x 40 mm
- Weight of transmitter: 126 g without auxillary battery
- Modulation: Digital Hopping System
- Carrier frequency: 2.4 GHz ISM Band
- Frequency response: 30 Hz – 20 KHz
- Signal to Noise ratio: > 75 dB
- THD: < 0,5 %
- Transmission range: Up to 25 meters (open area)
- Transmission power: 10 mW
- Audio-Inputs: 3.5 mm stereo jack socket and digital optical Toslink
- Power supply: Adapter: Primary 100 - 230V, 50-60 Hz, secondary 5 V DC, 550 mA
- Controls: Volume, L/R Balance, Tone control (3 presets)
- Size of stethoscope receiver (Height x Width x Depth): 229 mm x 135 mm x 28 mm
- Weight of stethoscope receiver: 68 g
- Maximum volume output of direct speakers: up to 120 dB
- Ambient temperature range : 0°C - 55°C
- Power supply of receivers: 3.7 V Lithium-polymer rechargeable battery, 350 mAh
- Usage time per full charge: 6 h - 8 h, depending on set volume
- Recharge time: approx. 3 h (2h for 90% charge)
- Country of Origin: People's Republic of China
- Conformities: CE, WEEE, RoHS